

Key **Features**

- Auto Power Off
- 22,000:1 contrast ratio
- SuperColor™ Technology
- 5 colour modes
- Vertical Keystone



Product **Description**

The ViewSonic SP3 offers impressive visual performance in small business meeting rooms and classrooms. With higher brightness and longer lamp life, the SP3 projector is guaranteed to reproduce the finest of details in any environment for much longer. ViewSonic exclusive SuperColor™ technology offers a wider range of displayable color ensuring true-to-life color accuracy in both bright and dark environments without sacrificing image quality.



1. Keypad 2. LED indicator 3. Lamp cover 8. Audio in/out 9. HDMI 10. Dual VGA 15. RS232

4. Security lock 5. Zoom/Focus 6. Front IR 7. Projection Lens 11. VGA out 12. Mini USB 13. Video 14. Kensington® Lock Slot

Visit Us

www.viewsonic.com

PM ViewS	onic SP3 4,800 ANSI Lumens SVG	GA Business Projector - Datasheet -	ViewSonic Malaysia
SPECIFICATION		STANDARD ACCESSORY	
Projection system:	0.55" SVGA	Power Cord:	1
Native Resolution:	800x600	VGA cable:	1
DC type:	DC3	Remote Control:	1
Brightness:	4,800 ANSI Lumens	QSG & CD:	QSG: 1 / CD: NA
Contrast Ratio with SuperEco mode:	22000:1	OPTIONAL ACCESSORY Air Filter:	RSPL
Display Color:	1.07 Billion Colors		
Light Source:	Lamp		
Light source life (Nor/SuperEco):	5000/15000		
Lamp Watt:	190W		
Lens:	F=2.56-2.68, f=22-24.1 mm		
Projection Offset:	120%+/-5%		
Throw Ratio:	1.96~2.15		
Image size:	30" - 300"		
Throw Distance:	1.19m-13.11m(100" @3.98m)		
Keystone:	±40° (Vertical)		
Optical Zoom:	1.1x		
Audible Noise (Eco):	27dB		
Resolution Support:	VGA(640 x 480) to FullHD(1920 x 1080)		
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p		
Video Compatibility:	NTSC, PAL, SECAM		
Horizontal Frequency:	15K~102KHz		
Vertical Scan Rate:	23~120Hz		
INPUT			
Computer in (share with component):	2		
Composite:	1		
Audio-in (3.5mm):	1		
HDMI:	1 (Back)		
OUTPUT			
Monitor out:	1		
Audio out (3.5mm):	1		
Speaker:	2W		
CONTROL			
RS232:	1		
USB type mini B (Services):	1		
OTHERS			
Power Supply Voltage:	100-240V+/- 10%, 50/60Hz AC		
Power Consumption:	Normal: 260W Standby: <0.5W		
Operating Temperature:	0~40°C		
Carton:	Brown		
Net Weight:	2.2kg		
Dimensions (WxDxH) w/adjustment foot:	294x218x110mm		
Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S- Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic,		
	Vietnamese		