

Key Features


- 22,000:1 contrast ratio
- SuperColor™ technology
- 5 colour modes
- · Auto power off
- Vertical keystone



Product **Description**

The ViewSonic SP7 offers impressive visual performance to improve presentations, ideal for use in small business meeting rooms and classrooms. Packed with 3500 ANSI Lumens of brightness and a 22,000:1 contrast ratio, this projector is guaranteed to reproduce the finest of details regardless of the amount of ambient lighting present. ViewSonic exclusive SuperColor™ technology offers a wider range of displayable color for projected images with true-to-life color accuracy. Users can choose from 5 color modes, including standard, brightest, presentation, photo, and movie mode, to select the mode that best suits their needs based on their usage scenario. In addition, the energy-saving SuperEco mode of SP7 reduces power consumption and extends the lamp life by up to 15,000 hours.





- Keypad
 LED indicator
 Lamp cover
- 4. Security lock
 5. Zoom/Focus
 6. Front IR
 7. Projection Lens

- 8. Audio in/out 9. HDMI 10. Dual VGA 11. VGA out 12. Mini USB 13. Video 14. Kensington® Lock Slot

15. RS232

Visit Us

www.viewsonic.com

SPECIFICATION

STANDARD ACCESSORY

SPECIFICATION	
Projection system:	0.65" WXGA
Native Resolution:	1280x800
DC type:	DC3
Brightness:	3500 ANSI lumens
Contrast Ratio with SuperEco mode:	22000:1
Display Color:	1.07 Billion Colors
Light Source:	Lamp
Light source life (Nor/SuperEco):	5000/15000
Lamp Watt:	200W
Lens:	F=2.56-2.68, f=22-24.1 mm
Projection Offset:	100%+/-5%
Throw Ratio:	1.55~1.70
Image size:	30" - 300"
Throw Distance:	1m-10.98m(100" @3.34m)
Keystone:	±40° (Vertical)
Optical Zoom:	1.1x
Audible Noise (Eco):	27dB
Resolution Support:	VGA(640 x 480) to FullHD(1920 x 1080)
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility:	NTSC, PAL, SECAM
Horizontal Frequency:	15K~102KHz
Vertical Scan Rate:	23~120Hz
INPUT	
Computer in (share with component):	2
Composite:	1
Audio-in (3.5mm):	1
HDMI:	1 (Back)
ОUТРUТ	
Monitor out:	1
Audio out (3.5mm):	1
Speaker:	2W
CONTROL	
RS232:	1
USB type mini B (Services): OTHERS	1
Power Supply Voltage:	100-240V+/- 10%, 50/60Hz AC
Power Consumption:	Normal: 260W Standby: <0.5W
Operating Temperature:	0~40°C
Carton:	Brown
Net Weight:	2.2kg
Dimensions (WxDxH) w/adjustment foot:	294x218x110mm
Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S- Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese

Power Cord:	1
VGA cable:	1
Remote Control:	1
QSG & CD:	QSG: 1 / CD: NA
OPTIONAL ACCESSORY	
Air Filter:	RSPL