

cloud



Outstanding Performance and Enhances Customer Experience

The sleek and elegant design of CPOS 320 Plus makes it a perfect fit to the retail and hospitality industry. With Intel's Bay Trail, the CPOS 320 Plus guarantees outstanding performance and enhances customer experience. Seamless integration of numerous peripheral modules such as MSR, Second Display and Customer Display

Performance that Boosts Productivity

- Choice of three processors: from a cost-efficient Celeron to a high-performance Core i5—offer scalable performance levels
- Up to 32 GB of high-speed memory offer sufficient headroom for future requirements

Tailored, Flexible Configurability

Configuration options allow the system to flexibly adapt to almost any requirement:

- Type and number of interfaces can be tailored to customer needs
- Additional I/O hubs expand the interface selection
- Adaptable peripherals save valuable counter space

Made for Retail, Built to Last

Cloud Advanced systems are designed and manufactured specifically for retail:

- Aluminum housing allows use in harsh and demanding environments
- Reinforced glass surface guarantees trouble-free touch usage
- Robust system design allows installations in environments with enhanced ambient temperature.



Delicate and cabinet design, better for space saving

Support wall-mounted function, more options for installation

Modular design (customer display), easy for disassembly

LCD supports over 10 years continuous service life time (Industrial grade A LCD, such as Sharp and Mitsubishi)

Metal Base design, works excellent on wet desktop(fording depth up to 10cm)

cloud

Processor	Choice of three processors: from a cost-efficient Celeron to a high-performance Core i5—offer scalable performance levels
Chipset	ITE Tech IT8786E
Memory	4GB Standard, DDR4L 2133 MT/s, Socket 1 x SODIMM (Max. 16GB)
Storage	SATA 3 (6Gb/s) 2.5 inch SSD 64GB, Support AHCI
OS	Windows 7, Windows 8.1, Windows 10 IoT Enterprise, POS Ready 7
Audio	Realtek ALC662-VD
Display	Type: 15" TFT LED Backlight Resolution: 1024 x 768 Brightness: 300 cd/m ² (typ.) Touch Screen: Projective Capacitive Touch
Interface	Display: 1 x VGA (With Power Output) LAN: 1 x Gigabit Ethernet, RJ-45 Audio: 1 x Line-out Power DC-IN: 1 x (3 Pin Connector) Extension Slot: mini PCIe, m-SATA
USB	6 (Rear 2, Back 4, USB 3.0 x 2, USB 2.0 x 4) 3 (Reserved for MSR, SCR, i-Button/Touch Controller/Camera), RJ-45
Serial Port	6 (COM 1 with 5V/12V Power Output on 9 Pins, BIOS) (COM2-3 RJ-45 , Full Signal) (COM5 Reserved for Cash Drawer Port)